R454b
Refrigerant

SUBMITTAL DATA SHEET

Series Name: EVOX Dual-Fuel System (Uncased Coil) Extreme Heat Series
Model Number: MAAHE-H36B-CA-UC/MO1HE-H30B-2A

Midea

Air Handler Heat Pump System	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:





INDOOR SPECIFICATION		
Dimension (W×D×H)	inch	19-5/8 x 22-3/4 x 20-3/8
	mm	499 x 578 x 518
Package (W×D×H)	inch	22-5/8 x 26-1/8 x 26-3/8
	mm	575 x 665 x 670
Net/Gross Weight	lbs	27.7 / 48.2
	kg	12.6 / 21.9

OUTDOOR SPECIFICATION		
Compressor Type		TWIN-ROTARY
Compressor Model		MTH356UKRC8FQL
Refrigerant		R454B
Refrigerant Oil Charge(mL)		1300
Refrigerant Oil		HAF68D1A
Outdoor Air Flow (Max) (CFM)		3,002
Outdoor Noise Level (dBA)		64
Dimension (W×D×H)	inch	37-1/4 x 16-1/8 x 31-7/8
	mm	946 × 410 × 810
Package (W×D×H)	inch	42-7/8 x 19-5/8 x 34-7/8
	mm	1,090 × 500 × 885
Net/Gross Weight	lbs	164 / 175
	kg	74.4 / 79.2

EFFICIENCY			
Cooling		Heating	
SEER2	16.0	HSPF2-4	9.6
EER2	11.0	COP	3.39


PERFORMANCE of Cooling	
Cooling (Btu/hr)	
Rated Capacity	29000
Min/Max Capacity	13,900 ~ 36,000
Moisture Removal(L/h)	3.7
Standard Operating Range(°F/°C)	-22~122 (-30 ~ 50)
Rated Cooling Conditions:	Indoor: 80°F DB/67°F WB
	Outdoor: 95°F DB/75°F WB


PERFORMANCE of Heating	
Heating (Btu/hr)	
1. @ 47°F Rated	30000
2. @ 47°F Min/Max Capacity	13,000 ~ 39,000
3. @ 17°F Rated	25000
4. @ 5°F Rated: Capacity / COP	32000/1.85
5. @ 5°F Max: Capacity	32000
Standard Operating Range(°F/°C)	-22~75 (-30 ~ 24)
1. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB
	Outdoor: 47°F DB/43°F WB
2. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB
	Outdoor: 17°F DB/15°F WB
3. Heating Conditions, Compressor	Indoor: 70°F DB/60°F WB
Operating at Max. Frequency	Outdoor: 5°F DB/5°F WB

ELECTRICAL	
Indoor Power Supply	24V,60Hz,1Ph
Indoor MCA 115V/(208/230V)	/
Indoor MOP	/
Outdoor Power Supply	208/230,60Hz,1Ph
Outdoor MCA	29.5
Outdoor MOP	30.0
Communication Wiring	AWG 20-2
Compressor RLA	20.5
Outdoor Fan Motor RLA	2.4
Outdoor Fan Motor W	/
Indoor Fan Motor RLA	/
Indoor Fan Motor W	/
System Power Input @ Cooling (W)	2640 (1,160 ~ 3,740)
System Power Input @ Heating (W)	2590 (1,090 ~ 3,480)
MCA: Min. circuit amps (A)	**MOCP: Max. over current protection (A)**
RLA: Rated load amps (A)	**W: Fan motor rated output (W)**

PIPING	
Throttle type(Indoor)	TXV
Throttle type(Outdoor)	EXV
Liquid Size	3/8" (9.52mm)
Gas Size	3/4" (19mm)
Max. Piping Length(ft/m)	164 (50)
Max. Height Difference(ft/m)	82 (25)
Max. Pre-charged Length(ft/m)	25 (7.5)
Refrigerant Pre-charged Amount(oz/kg)	106 (3)
Additional Charge of Refrigerant((oz/ft)/(g/m)	0.7 (65)
Connection Method	Flared


Indoor Unit Dimension






Outdoor Unit Dimension

Unit:inch(mm)



Installation Instruction For Outdoor Unit



Features

- Aluminum Coil
- Easy Maintenance
- Multiple control options available:
  - Wireless remote controller RG10
  - Two-way communication programmable wired controller with built-in Wi-Fi:120N(X6W) (Built-In)
  - Midea Smart Thermostat: MTL04-1
  - Third-Party 24V Thermostat
- Adaptive Control System
- Standard graphene fins, a standard feature of the outdoor unit, deliver superior corrosion resistance
- The outdoor unit comes standard with chassis and crankshaft electric heating
- Built-in Refrigerant Detection Sensor