R454b
Refrigerant

SUBMITTAL DATA SHEET

Series Name: EVOX Multi-Position Air Handler Extreme Heat Series
Model Number: MAUHE-H36B-2A/MO1HE-H36B-2A

Midea

Air Handler Heat Pump System	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



INDOOR SPECIFICATION		
ESP (in.W.C.)		0-0.8
Indoor Air Flow (Turbo/H/M/L/Si) (CFM)		1,189 / 1,083 / 971 / 865 / 865
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)		49 / 48.5 / 45.5 / 31 / 31
Dimension (W×D×H)	**inch**	21 x 21 x 49
	mm	534 × 534 × 1,245
Package (W×D×H)	**inch**	26-5/8 x 24-3/8 x 52-1/2
	mm	675 × 620 × 1,335
Net/Gross Weight	**lbs**	129 / 154
	kg	58.7 / 69.8

OUTDOOR SPECIFICATION		
Compressor Type		TWIN-ROTARY
Compressor Model		MTH356UKRC8FQL
Refrigerant		R454B
Refrigerant Oil Charge(mL)		1,300
Refrigerant Oil		HAF68D1A
Outdoor Air Flow (Max) (CFM)		3,002
Dimension (W×D×H)	**inch**	37-1/4 x 16-1/8 x 31-7/8
	mm	946 × 410 × 810
Package (W×D×H)	**inch**	42-7/8 x 19-5/8 x 34-7/8
	mm	1090 × 500 × 885
Net/Gross Weight	**lbs**	167 / 176
	kg	75.6 / 80

EFFICIENCY			
Cooling		**Heating**	
SEER2	16.5	**HSPF2-4**	8.2
EER2	10	**COP**	3.26

ELECTRICAL	
Indoor Power Supply	115/208/230V,60Hz,1Ph
Indoor MCA 115V/(208/230V)	8.0/6.0
Indoor MOP	15.0
Outdoor Power Supply	208/230V,60Hz,1Ph
Outdoor MCA	26.0
Outdoor MOP	30.0
Communication Wiring	AWG 20/2
Compressor RLA	18
Outdoor Fan Motor RLA	3.0
Outdoor Fan Motor W	150
Indoor Fan Motor RLA	4.5
Indoor Fan Motor W	375
System Power Input @ Cooling (W)	3,600(870 ~ 4,110)
System Power Input @ Heating (W)	3,330(530 ~ 3,500)
MCA: Min. circuit amps (A)	**MOCP: Max. over current protection (A)**
RLA: Rated load amps (A)	**W: Fan motor rated output (W)**


PERFORMANCE of Cooling	
Cooling (Btu/hr)	
Rated Capacity	36,000
Min/Max Capacity	7,900 ~ 36,800
Moisture Removal(L/h)	3.92
Standard Operating Range(°F/°C)	-22~122(-30 ~ 50)
Rated Cooling Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB


PERFORMANCE of Heating	
Heating (Btu/hr)	
1. @ 47°F Rated	37,000
2. @ 47°F Min/Max Capacity	7,500 ~ 38,000
3. @ 17°F Rated	23,200
4. @ 5°F Rated: Capacity / COP	32,000/1.85
5. @ 5°F Max: Capacity	32,000
Standard Operating Range(°F/°C)	-22~75 (-30 ~ 24)
1. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Heating Conditions, Compressor Operating at Max. Frequency	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB

PIPING	
Throttle type(Indoor)	EXV
Throttle type(Outdoor)	EXV
Liquid Size	3/8" (9.52mm)
Gas Size	3/4" (19mm)
Max. Piping Length(ft/m)	246 (75)
Max. Height Difference(ft/m)	98 (30)
Max. Pre-charged Length(ft/m)	25 (7.5)
Refrigerant Pre-charged Amount(oz/kg)	127 (3.6)
Additional Charge of Refrigerant(oz/ft)/(g/m)	0.7 (65)
Connection Method	Flared

Indoor Unit Dimension


Unit:inch(mm)






Outdoor Unit Dimension


Unit:inch(mm)




Installation Instruction For Outdoor Unit



Fan Performance For Indoor Unit



Outdoor Unit Sound Pressure Data



	Maximum Sound Pressure (dBA)				
Model	3'	5'	7'	9'	15'
MO1HE-H18B-2A	54.7	52.8	51.5	50.6	48.7
MO1HE-H24B-2A	55.9	54.0	52.7	51.8	49.9
MO1HE-H30B-2A	59.9	58.0	56.7	55.8	53.9
MO1HE-H36B-2A	60.2	58.3	57.0	56.1	54.2
MO1SE-H36B-2A	59.3	57.5	56.3	55.4	53.5
MO1HE-H42B-2A	60.9	59.0	57.7	56.8	54.9
MO1HE-H48B-2A	60.9	59.0	57.7	56.8	54.9
MO1SE-H48B-2A	62.1	60.2	58.9	58.0	56.1
MO1HE-H60B-2A	62.1	60.2	58.9	58.0	56.1

Features

- Multi-position installation: horizontal(left or right), vertical(up or down)
- The IDU supports 115/230V voltage compatibility
- Aluminum Coil
- Constant Air Flow system: Up to 0.8 In.W.C.
- Optional Auxiliary heat kit up to 25kW
- Easy Maintenance
- Multiple control options available:
  - Wireless remote controller RG10 (Built-In)
  - Two-way communication programmable wired controller with built-in Wi-Fi:120N(X6W)
  - Midea Smart Thermostat
  - Third-Party 24V Thermostat
- Adaptive Control System
- 100% heating output down to -4°F*
- Standard graphene fins, a standard feature of the outdoor unit, deliver superior corrosion resistance
- The outdoor unit comes standard with chassis and crankshaft electric heating
- Built-in Refrigerant Detection Sensor

* When MAUHE-H36B-2A is paired with MO1SE-H36B-2A, its rated heating capacity at -4°F is 100%