

R454b Refrigerant

SUBMITTAL DATA SHEET



Series Name: Advanced Heat WM AHU Series
Model Number: MAWHE-H24B-2A/MO1BE-H24B-2A

Air Handler Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



INDOOR SPECIFICATION

ESP(inWG)		0~0.8
Indoor Air Flow (Turbo/H/M/L/Si) (CFM)		824 / 759 / 695 / 630 / 630
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)		53 / 51 / 48 / 37.5 / 37.5
Dimension (W×D×H)	inch	20-1/4 x 15-3/4 x 36-1/2
	mm	515 × 399 × 928
Package (W×D×H)	inch	22-7/8 x 19-1/2 x 42-7/8
	mm	580 × 495 × 1090
Net/Gross Weight	lbs	91 / 111
	kg	41.5 / 50.5

OUTDOOR SPECIFICATION

Compressor Type		ROTARY
Compressor Model		KTM240D46UKT2
Refrigerant		R454B
Refrigerant Oil Charge(mL)		620
Refrigerant Oil		VG74
Outdoor Air Flow (Max) (CFM)		1,766
Outdoor Noise Level (dBA)		59
Dimension (W×D×H)	inch	35 x 13-1/2 x 26-1/2
	mm	890 × 342 × 673
Package (W×D×H)	inch	39-1/8 x 15-5/8 x 29-1/8
	mm	995 × 398 × 740
Net/Gross Weight	lbs	102 / 109
	kg	46.4 / 49.5

EFFICIENCY

Cooling		Heating	
SEER2	17.4	HSPF2-4	10.4
EER2	10.8	COP	3.80

PERFORMANCE of Cooling

Cooling (Btu/hr)	
Rated Capacity	24,000
Min/Max Capacity	10,100~27,500
Moisture Removal(L/h)	2.5
Standard Operating Range(*F/*C)	-13~122 (-25 ~ 50)
Rated Cooling Conditions:	
Indoor: 80°F DB/67°F WB	
Outdoor: 95°F DB/75°F WB	

PERFORMANCE of Heating

Heating (Btu/hr)	
1. @ 47°F Rated	25,000
2. @ 47°F Min/Max Capacity	7,000~32,200
3. @ 17°F Rated	20,800
4. @ 5°F Rated: Capacity / COP	19,400/1.96
5. @ 5°F Max: Capacity	19,600
Standard Operating Range(*F/*C)	-13~75 (-25 ~ 24)
1. Rated Heating Conditions:	
Indoor: 70°F DB/60°F WB	
Outdoor: 47°F DB/43°F WB	
2. Rated Heating Conditions:	
Indoor: 70°F DB/60°F WB	
Outdoor: 17°F DB/15°F WB	
3. Heating Conditions, Compressor Operating at Max. Frequency	
Indoor: 70°F DB/60°F WB	
Outdoor: 5°F DB/5°F WB	


ELECTRICAL

Indoor Power Supply	115/208/230V,60Hz,1Ph
Indoor MCA 115V/(208/230V)	4
Indoor MOP	15.0
Outdoor Power Supply	208/230V,60Hz,1Ph
Outdoor MCA	19.0
Outdoor MOP	20.0
Communication Wiring	AWG 20-2
Compressor RLA	14
Outdoor Fan Motor RLA	1
Outdoor Fan Motor W	/
Indoor Fan Motor RLA	3
Indoor Fan Motor W	250
System Power Input @ Cooling (W)	2,222 (830 ~ 2,850)
System Power Input @ Heating (W)	1,980 (455 ~2,590)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

PIPING

Throttle type(Indoor)	EXV
Throttle type(Outdoor)	EXV
Liquid Size	3/8" (9.52mm)
Gas Size	3/4" (19mm)
Max. Piping Length(ft/m)	164 (50)
Max. Height Difference(ft/m)	82 (25)
Max. Pre-charged Length(ft/m)	25 (7.5)
Refrigerant Pre-charged Amount(oz/kg)	74 (2.1)
Additional Charge of Refrigerant(oz/ft)/(g/m)	0.7 (65)
Connection Method	Flared


Indoor Unit Dimension




Dimensions		Model(Btu/h)		18K/24K		30K/36K	
				inch	mm	inch	mm
A	Model Height			36-1/2	928	40	1017
B	Model Width			20-1/4	515	22	559
C	Supply Air Opening Width			17-13/32	442	18-27/32	478.6
D	Return Air Opening Width			19-7/16	493.8	21-5/32	537.8
E	Model Depth			15-3/4	399	19	483
F	Supply Air Opening Depth			10-7/16	265.2	9-9/32	235.4
G	Return Air Opening Depth			10-9/32	261	13-2/32	332.5
H	Supply Air Opening Clearance			1-5/32	29.1	1-5/8	41
I	Return Air Opening Side Clearance			13/32	10.6	13/32	10.6
J	Return Air Opening Front Clearance			15/32	12	5/8	16

Outdoor Unit Dimension


Unit:inch(mm)



Installation Instruction For Outdoor Unit



Fan Performance For Indoor Unit



Features

- Multi-position of return air: front(factory standard) or bottom
- Aluminum Coil
- Constant Air Flow system: Up to 0.80 In.W.C.
- Optional Auxiliary heat kit up to 10kW
- Easy Maintenance
- Multiple control options available:
 - Two-way communication wired controller with built-in Wi-Fi: 120N (X6W)
 - Wireless remote control
 - Third-Party 24V Thermostat
- High efficiency up to 19.3 SEER2, 12.1 EER2, 10.8 HSPF2
- Base pan heater and crankcase heater are equipped as standard