

**R134a**  
Refrigerant

# SUBMITTAL DATA SHEET



Series Name: HPWH  
Model Number: **MCHW-65VN3A**

## Heat Pump Water Heater System

Location: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted to: \_\_\_\_\_  
 Submitted by: \_\_\_\_\_  
 Reference: \_\_\_\_\_

Approval: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Construction: \_\_\_\_\_  
 Unit #: \_\_\_\_\_  
 Drawing #: \_\_\_\_\_

<b>Product Code</b>	22025310000629
<b>Product Model</b>	MCHW-65VN3A
<b>Certified</b>	AHRI  Energy Star  UL 



## SYSTEM PERFORMANCE DATA


Power supply		
Normal Operational Voltage	(V, Ph, Hz)	240 V,1 Ph,60 Hz
Voltage Range	(V)	208-240
Electrical		
Minimum circuit ampacity	(A)	23.6 A (208 V) / 26.8 A (240 V)
Max.fuse	(A)	25 A (208 V) / 30 A (240 V)
Connection wiring		AWG 10/3
Energy information		
Normal Gallon Capacity	(Gallon)	65
Rated Gallon Capacity	(Gallon)	61
Uniform Energy Factor (UEF)		3.9
First Hour Rating (FHR)	(Gallon)	80
Water Outlet Temperature Range	(Deg. °F)	109-149
Upper Element Wattage	(W)	4500 (240 V)
Lower Element Wattage	(W)	4500 (240 V)
Compressor capacity	(W)	1500
Total Unit Wattage (input)	(W)	5500
Cold Climate Efficiency(CCE)		3
Recovery In G.P.H. 90° F Rise		27.5
Heat pump ambient operating range	(Deg. °F)	37-109
Element ambient operating range	(Deg. °F)	5-115
Sound	(dBA)	49.5

## UNIT DATA

Body Height	(inch)	65-7/8
Body Diameter(inch)	(inch)	25-3/4
Body Weight	(lbs)	271
Ship Length(inch)	(inch)	30-1/8 * 28-7/8
Ship Height(inch)	(inch)	75-5/8
Ship Weight(lbs)	(lbs)	334
Inlet Water Connection Size	(inch)	0.75
Outlet Water Connection Size	(inch)	0.75
Drainage Hose	(inch)	0.75
Installation Clearance (Back)	(inch)	0
Installation Clearance (side)	(inch)	6
Installation Clearance (top)	(inch)	20
Refrigerant Type		R134a
Refrigerant charge	oz	18
Loading quantity(40HQ)	pcs	45

Indoor Unit Dimension

Unit: inch (mm)




FEATURES



**Key components of Midea COMBO HPWH**

- Evaporator**  
Double-Layer heat transfer coil, compact size & high capacity
- Compressor**  
High Efficiency Rotary Compressor, R134a refrigerant, durable and silence
- Water Tank**  
Blue-Diamond Enamel Tank with +15 years lifespan
- Condenser Coil**  
Microchannel heat exchanger, higher heat exchange area and higher efficiency



**Leakage Detection**

- Leakage detection kit(Optional)
- Main PCB  
Leakage prevention algorithm contained.
- Leakage Detection Sensor  
Fix at the bottom of the unit, detect if water is leaking.
- Shut-off valve  
Automatically close the water inlet valve when water leakage happens. Prevent your house from flooding, protect your carpet and floor.

**Five modes**

Five modes, suitable for various usage scenarios

**Most saving**

**HP**  
**Heat Pump**  
Only the heat pump heat the water, most energy efficiently mode. Saving your electric bill significantly.

**Save & cozy**

**Economy**  
Calculate the demand automatically, save the bill & ensure comfortable usage

**Highest recovery**

**Hybrid**  
Element and Heat Pump works together, heat your water rapidly

**Freezing protect**


**Vacation**  
Protect the pipe system and water tank from frozen when you are away from home

**Backup Plan**

**Electric Heating**  
Only the element heat the water, for harsh days use, or emergency use.

**Demand Response Function**

**Build-in Demand Response Port**  
A CTA-2045 port that fits UCM module is at the top of the unit. Plug a UCM in and realize Demand Response function.



## **North American HVAC Products Ltd.**

---

Add.: #100 5118 N Fraser Wy, Burnaby, BC V5J 0H1

Tel: 604-430-8496 [info@nahvac.com](mailto:info@nahvac.com) [www.nahvac.com](http://www.nahvac.com)

Midea reserves the right to change the specifications of the product, and to withdraw or replace products without prior notification or public announcement.  
Midea is constantly developing and improving its products.